



CMJ8-POE-A-C5E



- POE++ compatible
- Category 5E compatible
- RJ45 Shielded connectors
- IEC 61643-21, EN 61643-21
- Outdoor application: IP65 rating
- Plastic enclosure
- Certified UL497B



	Electrical Characteristics																																					
 <p>P: 3-electrode GDT DBC: Low capacitance diode</p>	<table border="1"> <tr> <td>Network</td> <td></td> <td>Gigabit Ethernet (Cat.5E)</td> </tr> <tr> <td>Nominal line voltage</td> <td>Un</td> <td>48 Vdc</td> </tr> <tr> <td>Max. DC operating voltage</td> <td>Uc</td> <td>60 Vdc - 650 mA</td> </tr> <tr> <td>Max. frequency</td> <td>f max.</td> <td>250 MHz</td> </tr> <tr> <td>Max. data rate</td> <td></td> <td>10/100/1000 Mbps</td> </tr> <tr> <td>Insertion loss</td> <td></td> <td>< 1 dB</td> </tr> <tr> <td>Max. load current</td> <td>IL</td> <td>1200 mA</td> </tr> <tr> <td>Protection level Following the test category C3 (IEC61643-21) - Line/Line</td> <td>Up</td> <td>70 V</td> </tr> <tr> <td>Impulse current 2 x 10/350µs Test - D1 Category</td> <td>Iimp</td> <td>500 A</td> </tr> <tr> <td>Line/Line Nominal discharge current C2 Category</td> <td>In L/L</td> <td>500 A</td> </tr> <tr> <td>Line/Ground Nominal discharge current 8 /20µs Test x 10 - C2 Category</td> <td>In L/PE</td> <td>2000 A</td> </tr> </table>		Network		Gigabit Ethernet (Cat.5E)	Nominal line voltage	Un	48 Vdc	Max. DC operating voltage	Uc	60 Vdc - 650 mA	Max. frequency	f max.	250 MHz	Max. data rate		10/100/1000 Mbps	Insertion loss		< 1 dB	Max. load current	IL	1200 mA	Protection level Following the test category C3 (IEC61643-21) - Line/Line	Up	70 V	Impulse current 2 x 10/350µs Test - D1 Category	Iimp	500 A	Line/Line Nominal discharge current C2 Category	In L/L	500 A	Line/Ground Nominal discharge current 8 /20µs Test x 10 - C2 Category	In L/PE	2000 A			
Network		Gigabit Ethernet (Cat.5E)																																				
Nominal line voltage	Un	48 Vdc																																				
Max. DC operating voltage	Uc	60 Vdc - 650 mA																																				
Max. frequency	f max.	250 MHz																																				
Max. data rate		10/100/1000 Mbps																																				
Insertion loss		< 1 dB																																				
Max. load current	IL	1200 mA																																				
Protection level Following the test category C3 (IEC61643-21) - Line/Line	Up	70 V																																				
Impulse current 2 x 10/350µs Test - D1 Category	Iimp	500 A																																				
Line/Line Nominal discharge current C2 Category	In L/L	500 A																																				
Line/Ground Nominal discharge current 8 /20µs Test x 10 - C2 Category	In L/PE	2000 A																																				
Mechanical Characteristics																																						
<table border="1"> <tr> <td>Technology</td> <td></td> <td>GDT+Clamping diode</td> </tr> <tr> <td>SPD configuration</td> <td></td> <td>8 wires+shielded</td> </tr> <tr> <td>Connection to Network</td> <td></td> <td>RJ45 shielded connectors Female input/output</td> </tr> <tr> <td>Format</td> <td></td> <td>Plastic Box with connectors input/output</td> </tr> <tr> <td>Mounting</td> <td></td> <td>On plate or pole</td> </tr> <tr> <td>Housing material</td> <td></td> <td>Thermoplastic UL94 V-0</td> </tr> <tr> <td>Operating temperature</td> <td>Tu</td> <td>-40/+85°C</td> </tr> <tr> <td>Protection rating</td> <td></td> <td>IP65</td> </tr> <tr> <td>Failsafe mode</td> <td></td> <td>Short-circuit - transmission cut-off - fault mode 2</td> </tr> <tr> <td>Spare module(s)</td> <td></td> <td>CMJ8-POE-A-C5E/PCB</td> </tr> <tr> <td>Pinout</td> <td></td> <td>(1-2)(3-6)(4-5)(7-8)</td> </tr> <tr> <td>Dimensions</td> <td></td> <td>See diagram</td> </tr> </table>			Technology		GDT+Clamping diode	SPD configuration		8 wires+shielded	Connection to Network		RJ45 shielded connectors Female input/output	Format		Plastic Box with connectors input/output	Mounting		On plate or pole	Housing material		Thermoplastic UL94 V-0	Operating temperature	Tu	-40/+85°C	Protection rating		IP65	Failsafe mode		Short-circuit - transmission cut-off - fault mode 2	Spare module(s)		CMJ8-POE-A-C5E/PCB	Pinout		(1-2)(3-6)(4-5)(7-8)	Dimensions		See diagram
Technology		GDT+Clamping diode																																				
SPD configuration		8 wires+shielded																																				
Connection to Network		RJ45 shielded connectors Female input/output																																				
Format		Plastic Box with connectors input/output																																				
Mounting		On plate or pole																																				
Housing material		Thermoplastic UL94 V-0																																				
Operating temperature	Tu	-40/+85°C																																				
Protection rating		IP65																																				
Failsafe mode		Short-circuit - transmission cut-off - fault mode 2																																				
Spare module(s)		CMJ8-POE-A-C5E/PCB																																				
Pinout		(1-2)(3-6)(4-5)(7-8)																																				
Dimensions		See diagram																																				
Standards																																						
Standards compliance																																						
Certification		IEC 61643-21 / EN 61643-21 / UL497 B / IEEE 802-3ab/3at																																				
Part number																																						
892002																																						